



<http://www.eaglerip.com>

**Founder EagleRIP is a powerful Raster Image Processor (RIP), fully compatible with PostScript level 3 specifications, developed to satisfy customers' needs with its blazing speed, reliability, flexibility, comprehensive compatibility and consistent output.**

### **What's new in EagleRIP 3.0?**

- > Enhanced PDF interpretation
- > Support for the latest page layout software programs
- > Direct output of TIFF 1-bit files
- > Enhanced support for spot color
- > Multiple NT Pipe printing ports
- > Enhanced FM screening
- > New FM/AM hybrid screening (EagleFAM) option
- > New Ink Control option for digital printing
- > Support for automatic output of PS, PDF, EPS and TIFF files without postfix in HotFolder
- > Enhanced Rotate function



## Key Features

### > Enhanced PDF interpretation

- Founder's latest RIP technology with a built-in PDF native interpreter
- Improved compatibility of PDF file processing
- Free selection of BoundingBox in the PDF file

### > Comprehensive device support

100+ Devices include AGFA; Dainipon Screen; ECRM; FujiFilm; Scitex; Linotype-Hell; and so on.

### > Screening

Built-in (9): Round, Ellipse, Rhomb, Diamond, Square, PureRound, SharpEllipse, Cross and Founder FM.

Screening options (2): EagleAGS and EagleFAM.

### > Ganging

With this function, customer can compose different page size jobs on one plate.

### > Parameter Template

You can organize the parameter settings for different jobs. Set password to the templates to avoid careless operating. There is no limitation to templates for even different jobs and devices.

### > Powerful Preview function

User can preview the contents and effect for the output file on screen more conveniently.

## Minimum

- CPU: Pentium III 450 Mhz
- RAM: 128MB
- HDD: 10GB
- NIC: 10BASE-T Ethernet Interface Card
- OS: Windows NT Server 4.0, Windows NT Workstation 4.0, or Windows 2000

## Recommended

- CPU: Pentium 4, 2.0 GHz or above
- RAM: 512MB or above
- HDD: Ultra Wide SCSI (10,000rpm) hard disk
- Monitor: 1024 × 768, True color
- NIC: 10M/100M Ethernet adapter
- PCI slot: Compatible PCI protocol v2.0 or above
- OS: Windows 2000 Server or Windows XP Professional

# FOUNDER

**Beijing Founder Electronics Co., Ltd.**

No. 9, The 5th Street, Shangdi Information Industry Base  
Haidian District, Beijing 100085, P.R. China

Tel: +86 10 6298 1440

Fax: +86 10 6298 1438

For Support: EagleRIP\_Support@founder.com.cn